

TEXANA TANK CAR & MFG., LTD.

Gage Table Number: NTLX 2400 thru NTLX 2402
 Shell Full Capacity: 5,806 gal.
 Car Specification: DOT 111A100W1
 Tank Style: Straight cylindrical tank
 Tank Head Diameter: 108.0365 in.
 Tank Slope: 0 in/ft

Table Developed on: 6/7/06
 Printed on 6/7/06
 Printed by: R CALVIT
 Lining Thickness: 0 in.
 Volume of Internal Components: 0 gal.
 Manway Volume in Capacity: 0 gal.

| Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons |
|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|
| 0.25 | 1 | 10.25 | 247 | 20.25 | 700 | 30.25 | 1,277 |
| 0.50 | 2 | 10.50 | 256 | 20.50 | 713 | 30.50 | 1,292 |
| 0.75 | 4 | 10.75 | 266 | 20.75 | 726 | 30.75 | 1,308 |
| 1.00 | 7 | 11.00 | 275 | 21.00 | 739 | 31.00 | 1,323 |
| 1.25 | 10 | 11.25 | 285 | 21.25 | 753 | 31.25 | 1,339 |
| 1.50 | 13 | 11.50 | 295 | 21.50 | 766 | 31.50 | 1,355 |
| 1.75 | 16 | 11.75 | 305 | 21.75 | 779 | 31.75 | 1,371 |
| 2.00 | 20 | 12.00 | 315 | 22.00 | 793 | 32.00 | 1,387 |
| 2.25 | 24 | 12.25 | 325 | 22.25 | 807 | 32.25 | 1,403 |
| 2.50 | 28 | 12.50 | 335 | 22.50 | 820 | 32.50 | 1,419 |
| 2.75 | 33 | 12.75 | 345 | 22.75 | 834 | 32.75 | 1,435 |
| 3.00 | 37 | 13.00 | 356 | 23.00 | 848 | 33.00 | 1,451 |
| 3.25 | 42 | 13.25 | 366 | 23.25 | 862 | 33.25 | 1,467 |
| 3.50 | 47 | 13.50 | 377 | 23.50 | 876 | 33.50 | 1,483 |
| 3.75 | 53 | 13.75 | 388 | 23.75 | 890 | 33.75 | 1,499 |
| 4.00 | 58 | 14.00 | 399 | 24.00 | 904 | 34.00 | 1,515 |
| 4.25 | 64 | 14.25 | 409 | 24.25 | 918 | 34.25 | 1,532 |
| 4.50 | 70 | 14.50 | 421 | 24.50 | 932 | 34.50 | 1,548 |
| 4.75 | 76 | 14.75 | 432 | 24.75 | 947 | 34.75 | 1,564 |
| 5.00 | 82 | 15.00 | 443 | 25.00 | 961 | 35.00 | 1,581 |
| 5.25 | 88 | 15.25 | 454 | 25.25 | 976 | 35.25 | 1,597 |
| 5.50 | 95 | 15.50 | 466 | 25.50 | 990 | 35.50 | 1,614 |
| 5.75 | 101 | 15.75 | 477 | 25.75 | 1,005 | 35.75 | 1,630 |
| 6.00 | 108 | 16.00 | 489 | 26.00 | 1,019 | 36.00 | 1,647 |
| 6.25 | 115 | 16.25 | 501 | 26.25 | 1,034 | 36.25 | 1,663 |
| 6.50 | 122 | 16.50 | 512 | 26.50 | 1,049 | 36.50 | 1,680 |
| 6.75 | 130 | 16.75 | 524 | 26.75 | 1,064 | 36.75 | 1,697 |
| 7.00 | 137 | 17.00 | 536 | 27.00 | 1,078 | 37.00 | 1,713 |
| 7.25 | 145 | 17.25 | 548 | 27.25 | 1,093 | 37.25 | 1,730 |
| 7.50 | 153 | 17.50 | 560 | 27.50 | 1,108 | 37.50 | 1,747 |
| 7.75 | 161 | 17.75 | 573 | 27.75 | 1,123 | 37.75 | 1,764 |
| 8.00 | 169 | 18.00 | 585 | 28.00 | 1,138 | 38.00 | 1,780 |
| 8.25 | 177 | 18.25 | 597 | 28.25 | 1,154 | 38.25 | 1,797 |
| 8.50 | 185 | 18.50 | 610 | 28.50 | 1,169 | 38.50 | 1,814 |
| 8.75 | 194 | 18.75 | 622 | 28.75 | 1,184 | 38.75 | 1,831 |
| 9.00 | 202 | 19.00 | 635 | 29.00 | 1,199 | 39.00 | 1,848 |
| 9.25 | 211 | 19.25 | 648 | 29.25 | 1,215 | 39.25 | 1,865 |
| 9.50 | 220 | 19.50 | 661 | 29.50 | 1,230 | 39.50 | 1,882 |
| 9.75 | 229 | 19.75 | 674 | 29.75 | 1,245 | 39.75 | 1,899 |
| 10.00 | 238 | 20.00 | 687 | 30.00 | 1,261 | 40.00 | 1,916 |

This gage table shows OUTAGE volumes (volume of vapor space above the liquid surface).
 Distances are measured downward from the shell-full (zero-outage) level to the surface of the liquid.

TEXANA TANK CAR & MFG., LTD.

Gage Table Number: NTLX 2400
 Shell Full Capacity: 5,806 gal.
 Car Specification: DOT 111A100W1
 Tank Style: Straight cylindrical tank
 Tank Head Diameter: 108.0365 in.
 Tank Slope: 0 in/ft

Table Developed on: 6/7/06
 Printed on 6/7/06
 Printed by: R CALVIT
 Lining Thickness: 0 in.
 Volume of Internal Components: 0 gal.
 Manway Volume in Capacity: 0 gal.

Page 2

| Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons |
|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|
| 40.25 | 1,933 | 50.25 | 2,634 | 60.25 | 3,347 | 70.25 | 4,040 |
| 40.50 | 1,950 | 50.50 | 2,652 | 60.50 | 3,365 | 70.50 | 4,057 |
| 40.75 | 1,967 | 50.75 | 2,670 | 60.75 | 3,382 | 70.75 | 4,073 |
| 41.00 | 1,985 | 51.00 | 2,688 | 61.00 | 3,400 | 71.00 | 4,090 |
| 41.25 | 2,002 | 51.25 | 2,705 | 61.25 | 3,418 | 71.25 | 4,107 |
| 41.50 | 2,019 | 51.50 | 2,723 | 61.50 | 3,435 | 71.50 | 4,124 |
| 41.75 | 2,036 | 51.75 | 2,741 | 61.75 | 3,453 | 71.75 | 4,140 |
| 42.00 | 2,054 | 52.00 | 2,759 | 62.00 | 3,470 | 72.00 | 4,157 |
| 42.25 | 2,071 | 52.25 | 2,777 | 62.25 | 3,488 | 72.25 | 4,173 |
| 42.50 | 2,088 | 52.50 | 2,795 | 62.50 | 3,506 | 72.50 | 4,190 |
| 42.75 | 2,106 | 52.75 | 2,812 | 62.75 | 3,523 | 72.75 | 4,206 |
| 43.00 | 2,123 | 53.00 | 2,830 | 63.00 | 3,541 | 73.00 | 4,223 |
| 43.25 | 2,140 | 53.25 | 2,848 | 63.25 | 3,558 | 73.25 | 4,239 |
| 43.50 | 2,158 | 53.50 | 2,866 | 63.50 | 3,576 | 73.50 | 4,255 |
| 43.75 | 2,175 | 53.75 | 2,884 | 63.75 | 3,593 | 73.75 | 4,272 |
| 44.00 | 2,193 | 54.00 | 2,902 | 64.00 | 3,611 | 74.00 | 4,288 |
| 44.25 | 2,210 | 54.25 | 2,920 | 64.25 | 3,628 | 74.25 | 4,304 |
| 44.50 | 2,228 | 54.50 | 2,937 | 64.50 | 3,646 | 74.50 | 4,321 |
| 44.75 | 2,245 | 54.75 | 2,955 | 64.75 | 3,663 | 74.75 | 4,337 |
| 45.00 | 2,263 | 55.00 | 2,973 | 65.00 | 3,680 | 75.00 | 4,353 |
| 45.25 | 2,280 | 55.25 | 2,991 | 65.25 | 3,698 | 75.25 | 4,369 |
| 45.50 | 2,298 | 55.50 | 3,009 | 65.50 | 3,715 | 75.50 | 4,385 |
| 45.75 | 2,315 | 55.75 | 3,027 | 65.75 | 3,732 | 75.75 | 4,401 |
| 46.00 | 2,333 | 56.00 | 3,044 | 66.00 | 3,750 | 76.00 | 4,417 |
| 46.25 | 2,351 | 56.25 | 3,062 | 66.25 | 3,767 | 76.25 | 4,433 |
| 46.50 | 2,368 | 56.50 | 3,080 | 66.50 | 3,784 | 76.50 | 4,449 |
| 46.75 | 2,386 | 56.75 | 3,098 | 66.75 | 3,802 | 76.75 | 4,464 |
| 47.00 | 2,403 | 57.00 | 3,116 | 67.00 | 3,819 | 77.00 | 4,480 |
| 47.25 | 2,421 | 57.25 | 3,134 | 67.25 | 3,836 | 77.25 | 4,496 |
| 47.50 | 2,439 | 57.50 | 3,151 | 67.50 | 3,853 | 77.50 | 4,512 |
| 47.75 | 2,457 | 57.75 | 3,169 | 67.75 | 3,870 | 77.75 | 4,527 |
| 48.00 | 2,474 | 58.00 | 3,187 | 68.00 | 3,887 | 78.00 | 4,543 |
| 48.25 | 2,492 | 58.25 | 3,205 | 68.25 | 3,904 | 78.25 | 4,558 |
| 48.50 | 2,510 | 58.50 | 3,223 | 68.50 | 3,921 | 78.50 | 4,574 |
| 48.75 | 2,527 | 58.75 | 3,240 | 68.75 | 3,938 | 78.75 | 4,589 |
| 49.00 | 2,545 | 59.00 | 3,258 | 69.00 | 3,955 | 79.00 | 4,604 |
| 49.25 | 2,563 | 59.25 | 3,276 | 69.25 | 3,972 | 79.25 | 4,620 |
| 49.50 | 2,581 | 59.50 | 3,294 | 69.50 | 3,989 | 79.50 | 4,635 |
| 49.75 | 2,598 | 59.75 | 3,311 | 69.75 | 4,006 | 79.75 | 4,650 |
| 50.00 | 2,616 | 60.00 | 3,329 | 70.00 | 4,023 | 80.00 | 4,665 |

This gage table shows OUTAGE volumes (volume of vapor space above the liquid surface).
 Distances are measured downward from the shell-full (zero-outage) level to the surface of the liquid.

TEXANA TANK CAR & MFG., LTD.

Gage Table Number: NTLX 2400
 Shell Full Capacity: 5,806 gal.
 Car Specification: DOT 111A100W1
 Tank Style: Straight cylindrical tank
 Tank Head Diameter: 108.0365 in.
 Tank Slope: 0 in/ft

Table Developed on: 6/7/06
 Printed on 6/7/06
 Printed by: R CALVIT
 Lining Thickness: 0 in.
 Volume of Internal Components: 0 gal.
 Manway Volume in Capacity: 0 gal.

| Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons |
|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|
| 80.25 | 4,680 | 90.25 | 5,231 | 100.25 | 5,644 | | |
| 80.50 | 4,695 | 90.50 | 5,244 | 100.50 | 5,652 | | |
| 80.75 | 4,710 | 90.75 | 5,256 | 100.75 | 5,660 | | |
| 81.00 | 4,725 | 91.00 | 5,268 | 101.00 | 5,668 | | |
| 81.25 | 4,740 | 91.25 | 5,280 | 101.25 | 5,675 | | |
| 81.50 | 4,755 | 91.50 | 5,292 | 101.50 | 5,682 | | |
| 81.75 | 4,770 | 91.75 | 5,304 | 101.75 | 5,690 | | |
| 82.00 | 4,784 | 92.00 | 5,315 | 102.00 | 5,697 | | |
| 82.25 | 4,799 | 92.25 | 5,327 | 102.25 | 5,704 | | |
| 82.50 | 4,814 | 92.50 | 5,339 | 102.50 | 5,710 | | |
| 82.75 | 4,828 | 92.75 | 5,350 | 102.75 | 5,717 | | |
| 83.00 | 4,843 | 93.00 | 5,361 | 103.00 | 5,723 | | |
| 83.25 | 4,857 | 93.25 | 5,373 | 103.25 | 5,729 | | |
| 83.50 | 4,871 | 93.50 | 5,384 | 103.50 | 5,736 | | |
| 83.75 | 4,886 | 93.75 | 5,395 | 103.75 | 5,741 | | |
| 84.00 | 4,900 | 94.00 | 5,406 | 104.00 | 5,747 | | |
| 84.25 | 4,914 | 94.25 | 5,417 | 104.25 | 5,753 | | |
| 84.50 | 4,928 | 94.50 | 5,427 | 104.50 | 5,758 | | |
| 84.75 | 4,942 | 94.75 | 5,438 | 104.75 | 5,763 | | |
| 85.00 | 4,956 | 95.00 | 5,449 | 105.00 | 5,768 | | |
| 85.25 | 4,970 | 95.25 | 5,459 | 105.25 | 5,773 | | |
| 85.50 | 4,984 | 95.50 | 5,469 | 105.50 | 5,777 | | |
| 85.75 | 4,997 | 95.75 | 5,480 | 105.75 | 5,781 | | |
| 86.00 | 5,011 | 96.00 | 5,490 | 106.00 | 5,785 | | |
| 86.25 | 5,024 | 96.25 | 5,500 | 106.25 | 5,789 | | |
| 86.50 | 5,038 | 96.50 | 5,510 | 106.50 | 5,793 | | |
| 86.75 | 5,051 | 96.75 | 5,520 | 106.75 | 5,796 | | |
| 87.00 | 5,065 | 97.00 | 5,529 | 107.00 | 5,799 | | |
| 87.25 | 5,078 | 97.25 | 5,539 | 107.25 | 5,801 | | |
| 87.50 | 5,091 | 97.50 | 5,548 | 107.50 | 5,803 | | |
| 87.75 | 5,104 | 97.75 | 5,558 | 107.75 | 5,805 | | |
| 88.00 | 5,117 | 98.00 | 5,567 | 108.00 | 5,806 | | |
| 88.25 | 5,130 | 98.25 | 5,576 | | | | |
| 88.50 | 5,143 | 98.50 | 5,585 | | | | |
| 88.75 | 5,156 | 98.75 | 5,594 | | | | |
| 89.00 | 5,169 | 99.00 | 5,603 | | | | |
| 89.25 | 5,182 | 99.25 | 5,611 | | | | |
| 89.50 | 5,194 | 99.50 | 5,620 | | | | |
| 89.75 | 5,207 | 99.75 | 5,628 | | | | |
| 90.00 | 5,219 | 100.00 | 5,636 | | | | |

This gage table shows OUTAGE volumes (volume of vapor space above the liquid surface). Distances are measured downward from the shell-full (zero-outage) level to the surface of the liquid.

TEXANA TANK CAR & MFG., LTD.

Gage Table Number: NTLX 2400 thru NTLX 2402
 Shell Full Capacity: 5,806 gal.
 Car Specification: DOT 111A100W1
 Tank Style: Straight cylindrical tank
 Tank Head Diameter: 108.0365 in.
 Tank Slope: 0 in/ft

Table Developed on: 6/7/06
 Printed on 6/7/06
 Printed by: R CALVIT
 Lining Thickness: 0 in.
 Volume of Internal Components: 0 gal.
 Manway Volume in Capacity: 0 gal.

| Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons |
|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|
| 0.25 | 1 | 10.25 | 247 | 20.25 | 700 | 30.25 | 1,277 |
| 0.50 | 2 | 10.50 | 256 | 20.50 | 713 | 30.50 | 1,292 |
| 0.75 | 4 | 10.75 | 266 | 20.75 | 726 | 30.75 | 1,308 |
| 1.00 | 7 | 11.00 | 275 | 21.00 | 739 | 31.00 | 1,323 |
| 1.25 | 10 | 11.25 | 285 | 21.25 | 753 | 31.25 | 1,339 |
| 1.50 | 13 | 11.50 | 295 | 21.50 | 766 | 31.50 | 1,355 |
| 1.75 | 16 | 11.75 | 305 | 21.75 | 779 | 31.75 | 1,371 |
| 2.00 | 20 | 12.00 | 315 | 22.00 | 793 | 32.00 | 1,387 |
| 2.25 | 24 | 12.25 | 325 | 22.25 | 807 | 32.25 | 1,403 |
| 2.50 | 28 | 12.50 | 335 | 22.50 | 820 | 32.50 | 1,419 |
| 2.75 | 33 | 12.75 | 345 | 22.75 | 834 | 32.75 | 1,435 |
| 3.00 | 37 | 13.00 | 356 | 23.00 | 848 | 33.00 | 1,451 |
| 3.25 | 42 | 13.25 | 366 | 23.25 | 862 | 33.25 | 1,467 |
| 3.50 | 47 | 13.50 | 377 | 23.50 | 876 | 33.50 | 1,483 |
| 3.75 | 53 | 13.75 | 388 | 23.75 | 890 | 33.75 | 1,499 |
| 4.00 | 58 | 14.00 | 399 | 24.00 | 904 | 34.00 | 1,515 |
| 4.25 | 64 | 14.25 | 409 | 24.25 | 918 | 34.25 | 1,532 |
| 4.50 | 70 | 14.50 | 421 | 24.50 | 932 | 34.50 | 1,548 |
| 4.75 | 76 | 14.75 | 432 | 24.75 | 947 | 34.75 | 1,564 |
| 5.00 | 82 | 15.00 | 443 | 25.00 | 961 | 35.00 | 1,581 |
| 5.25 | 88 | 15.25 | 454 | 25.25 | 976 | 35.25 | 1,597 |
| 5.50 | 95 | 15.50 | 466 | 25.50 | 990 | 35.50 | 1,614 |
| 5.75 | 101 | 15.75 | 477 | 25.75 | 1,005 | 35.75 | 1,630 |
| 6.00 | 108 | 16.00 | 489 | 26.00 | 1,019 | 36.00 | 1,647 |
| 6.25 | 115 | 16.25 | 501 | 26.25 | 1,034 | 36.25 | 1,663 |
| 6.50 | 122 | 16.50 | 512 | 26.50 | 1,049 | 36.50 | 1,680 |
| 6.75 | 130 | 16.75 | 524 | 26.75 | 1,064 | 36.75 | 1,697 |
| 7.00 | 137 | 17.00 | 536 | 27.00 | 1,078 | 37.00 | 1,713 |
| 7.25 | 145 | 17.25 | 548 | 27.25 | 1,093 | 37.25 | 1,730 |
| 7.50 | 153 | 17.50 | 560 | 27.50 | 1,108 | 37.50 | 1,747 |
| 7.75 | 161 | 17.75 | 573 | 27.75 | 1,123 | 37.75 | 1,764 |
| 8.00 | 169 | 18.00 | 585 | 28.00 | 1,138 | 38.00 | 1,780 |
| 8.25 | 177 | 18.25 | 597 | 28.25 | 1,154 | 38.25 | 1,797 |
| 8.50 | 185 | 18.50 | 610 | 28.50 | 1,169 | 38.50 | 1,814 |
| 8.75 | 194 | 18.75 | 622 | 28.75 | 1,184 | 38.75 | 1,831 |
| 9.00 | 202 | 19.00 | 635 | 29.00 | 1,199 | 39.00 | 1,848 |
| 9.25 | 211 | 19.25 | 648 | 29.25 | 1,215 | 39.25 | 1,865 |
| 9.50 | 220 | 19.50 | 661 | 29.50 | 1,230 | 39.50 | 1,882 |
| 9.75 | 229 | 19.75 | 674 | 29.75 | 1,245 | 39.75 | 1,899 |
| 10.00 | 238 | 20.00 | 687 | 30.00 | 1,261 | 40.00 | 1,916 |

This gage table shows OUTAGE volumes (volume of vapor space above the liquid surface).
 Distances are measured downward from the shell-full (zero-outage) level to the surface of the liquid.

TEXANA TANK CAR & MFG., LTD.

Gage Table Number: NTLX 2400
 Shell Full Capacity: 5,806 gal.
 Car Specification: DOT 111A100W1
 Tank Style: Straight cylindrical tank
 Tank Head Diameter: 108.0365 in.
 Tank Slope: 0 in/ft

Table Developed on: 6/7/06
 Printed on 6/7/06
 Printed by: R CALVIT
 Lining Thickness: 0 in.
 Volume of Internal Components: 0 gal.
 Manway Volume in Capacity: 0 gal.

Page 2

| Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons |
|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|
| 40.25 | 1,933 | 50.25 | 2,634 | 60.25 | 3,347 | 70.25 | 4,040 |
| 40.50 | 1,950 | 50.50 | 2,652 | 60.50 | 3,365 | 70.50 | 4,057 |
| 40.75 | 1,967 | 50.75 | 2,670 | 60.75 | 3,382 | 70.75 | 4,073 |
| 41.00 | 1,985 | 51.00 | 2,688 | 61.00 | 3,400 | 71.00 | 4,090 |
| 41.25 | 2,002 | 51.25 | 2,705 | 61.25 | 3,418 | 71.25 | 4,107 |
| 41.50 | 2,019 | 51.50 | 2,723 | 61.50 | 3,435 | 71.50 | 4,124 |
| 41.75 | 2,036 | 51.75 | 2,741 | 61.75 | 3,453 | 71.75 | 4,140 |
| 42.00 | 2,054 | 52.00 | 2,759 | 62.00 | 3,470 | 72.00 | 4,157 |
| 42.25 | 2,071 | 52.25 | 2,777 | 62.25 | 3,488 | 72.25 | 4,173 |
| 42.50 | 2,088 | 52.50 | 2,795 | 62.50 | 3,506 | 72.50 | 4,190 |
| 42.75 | 2,106 | 52.75 | 2,812 | 62.75 | 3,523 | 72.75 | 4,206 |
| 43.00 | 2,123 | 53.00 | 2,830 | 63.00 | 3,541 | 73.00 | 4,223 |
| 43.25 | 2,140 | 53.25 | 2,848 | 63.25 | 3,558 | 73.25 | 4,239 |
| 43.50 | 2,158 | 53.50 | 2,866 | 63.50 | 3,576 | 73.50 | 4,255 |
| 43.75 | 2,175 | 53.75 | 2,884 | 63.75 | 3,593 | 73.75 | 4,272 |
| 44.00 | 2,193 | 54.00 | 2,902 | 64.00 | 3,611 | 74.00 | 4,288 |
| 44.25 | 2,210 | 54.25 | 2,920 | 64.25 | 3,628 | 74.25 | 4,304 |
| 44.50 | 2,228 | 54.50 | 2,937 | 64.50 | 3,646 | 74.50 | 4,321 |
| 44.75 | 2,245 | 54.75 | 2,955 | 64.75 | 3,663 | 74.75 | 4,337 |
| 45.00 | 2,263 | 55.00 | 2,973 | 65.00 | 3,680 | 75.00 | 4,353 |
| 45.25 | 2,280 | 55.25 | 2,991 | 65.25 | 3,698 | 75.25 | 4,369 |
| 45.50 | 2,298 | 55.50 | 3,009 | 65.50 | 3,715 | 75.50 | 4,385 |
| 45.75 | 2,315 | 55.75 | 3,027 | 65.75 | 3,732 | 75.75 | 4,401 |
| 46.00 | 2,333 | 56.00 | 3,044 | 66.00 | 3,750 | 76.00 | 4,417 |
| 46.25 | 2,351 | 56.25 | 3,062 | 66.25 | 3,767 | 76.25 | 4,433 |
| 46.50 | 2,368 | 56.50 | 3,080 | 66.50 | 3,784 | 76.50 | 4,449 |
| 46.75 | 2,386 | 56.75 | 3,098 | 66.75 | 3,802 | 76.75 | 4,464 |
| 47.00 | 2,403 | 57.00 | 3,116 | 67.00 | 3,819 | 77.00 | 4,480 |
| 47.25 | 2,421 | 57.25 | 3,134 | 67.25 | 3,836 | 77.25 | 4,496 |
| 47.50 | 2,439 | 57.50 | 3,151 | 67.50 | 3,853 | 77.50 | 4,512 |
| 47.75 | 2,457 | 57.75 | 3,169 | 67.75 | 3,870 | 77.75 | 4,527 |
| 48.00 | 2,474 | 58.00 | 3,187 | 68.00 | 3,887 | 78.00 | 4,543 |
| 48.25 | 2,492 | 58.25 | 3,205 | 68.25 | 3,904 | 78.25 | 4,558 |
| 48.50 | 2,510 | 58.50 | 3,223 | 68.50 | 3,921 | 78.50 | 4,574 |
| 48.75 | 2,527 | 58.75 | 3,240 | 68.75 | 3,938 | 78.75 | 4,589 |
| 49.00 | 2,545 | 59.00 | 3,258 | 69.00 | 3,955 | 79.00 | 4,604 |
| 49.25 | 2,563 | 59.25 | 3,276 | 69.25 | 3,972 | 79.25 | 4,620 |
| 49.50 | 2,581 | 59.50 | 3,294 | 69.50 | 3,989 | 79.50 | 4,635 |
| 49.75 | 2,598 | 59.75 | 3,311 | 69.75 | 4,006 | 79.75 | 4,650 |
| 50.00 | 2,616 | 60.00 | 3,329 | 70.00 | 4,023 | 80.00 | 4,665 |

This gage table shows OUTAGE volumes (volume of vapor space above the liquid surface).
 Distances are measured downward from the shell-full (zero-outage) level to the surface of the liquid.

TEXANA TANK CAR & MFG., LTD.

Gage Table Number: NTLX 2400
 Shell Full Capacity: 5,806 gal.
 Car Specification: DOT 111A100W1
 Tank Style: Straight cylindrical tank
 Tank Head Diameter: 108.0365 in.
 Tank Slope: 0 in/ft

Table Developed on: 6/7/06
 Printed on 6/7/06
 Printed by: R CALVIT
 Lining Thickness: 0 in.
 Volume of Internal Components: 0 gal.
 Manway Volume in Capacity: 0 gal.

| Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons |
|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|
| 80.25 | 4,680 | 90.25 | 5,231 | 100.25 | 5,644 | | |
| 80.50 | 4,695 | 90.50 | 5,244 | 100.50 | 5,652 | | |
| 80.75 | 4,710 | 90.75 | 5,256 | 100.75 | 5,660 | | |
| 81.00 | 4,725 | 91.00 | 5,268 | 101.00 | 5,668 | | |
| 81.25 | 4,740 | 91.25 | 5,280 | 101.25 | 5,675 | | |
| 81.50 | 4,755 | 91.50 | 5,292 | 101.50 | 5,682 | | |
| 81.75 | 4,770 | 91.75 | 5,304 | 101.75 | 5,690 | | |
| 82.00 | 4,784 | 92.00 | 5,315 | 102.00 | 5,697 | | |
| 82.25 | 4,799 | 92.25 | 5,327 | 102.25 | 5,704 | | |
| 82.50 | 4,814 | 92.50 | 5,339 | 102.50 | 5,710 | | |
| 82.75 | 4,828 | 92.75 | 5,350 | 102.75 | 5,717 | | |
| 83.00 | 4,843 | 93.00 | 5,361 | 103.00 | 5,723 | | |
| 83.25 | 4,857 | 93.25 | 5,373 | 103.25 | 5,729 | | |
| 83.50 | 4,871 | 93.50 | 5,384 | 103.50 | 5,736 | | |
| 83.75 | 4,886 | 93.75 | 5,395 | 103.75 | 5,741 | | |
| 84.00 | 4,900 | 94.00 | 5,406 | 104.00 | 5,747 | | |
| 84.25 | 4,914 | 94.25 | 5,417 | 104.25 | 5,753 | | |
| 84.50 | 4,928 | 94.50 | 5,427 | 104.50 | 5,758 | | |
| 84.75 | 4,942 | 94.75 | 5,438 | 104.75 | 5,763 | | |
| 85.00 | 4,956 | 95.00 | 5,449 | 105.00 | 5,768 | | |
| 85.25 | 4,970 | 95.25 | 5,459 | 105.25 | 5,773 | | |
| 85.50 | 4,984 | 95.50 | 5,469 | 105.50 | 5,777 | | |
| 85.75 | 4,997 | 95.75 | 5,480 | 105.75 | 5,781 | | |
| 86.00 | 5,011 | 96.00 | 5,490 | 106.00 | 5,785 | | |
| 86.25 | 5,024 | 96.25 | 5,500 | 106.25 | 5,789 | | |
| 86.50 | 5,038 | 96.50 | 5,510 | 106.50 | 5,793 | | |
| 86.75 | 5,051 | 96.75 | 5,520 | 106.75 | 5,796 | | |
| 87.00 | 5,065 | 97.00 | 5,529 | 107.00 | 5,799 | | |
| 87.25 | 5,078 | 97.25 | 5,539 | 107.25 | 5,801 | | |
| 87.50 | 5,091 | 97.50 | 5,548 | 107.50 | 5,803 | | |
| 87.75 | 5,104 | 97.75 | 5,558 | 107.75 | 5,805 | | |
| 88.00 | 5,117 | 98.00 | 5,567 | 108.00 | 5,806 | | |
| 88.25 | 5,130 | 98.25 | 5,576 | | | | |
| 88.50 | 5,143 | 98.50 | 5,585 | | | | |
| 88.75 | 5,156 | 98.75 | 5,594 | | | | |
| 89.00 | 5,169 | 99.00 | 5,603 | | | | |
| 89.25 | 5,182 | 99.25 | 5,611 | | | | |
| 89.50 | 5,194 | 99.50 | 5,620 | | | | |
| 89.75 | 5,207 | 99.75 | 5,628 | | | | |
| 90.00 | 5,219 | 100.00 | 5,636 | | | | |

This gage table shows OUTAGE volumes (volume of vapor space above the liquid surface). Distances are measured downward from the shell-full (zero-outage) level to the surface of the liquid.

TEXANA TANK CAR & MFG., LTD.

Gage Table Number: NTLX 2400 thru NTLX 2402
 Shell Full Capacity: 5,806 gal.
 Car Specification: DOT 111A100W1
 Tank Style: Straight cylindrical tank
 Tank Head Diameter: 108.0365 in.
 Tank Slope: 0 in/ft

Table Developed on: 6/7/06
 Printed on 6/7/06
 Printed by: R CALVIT
 Lining Thickness: 0 in.
 Volume of Internal Components: 0 gal.
 Manway Volume in Capacity: 0 gal.

| Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons |
|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|
| 0.25 | 1 | 10.25 | 247 | 20.25 | 700 | 30.25 | 1,277 |
| 0.50 | 2 | 10.50 | 256 | 20.50 | 713 | 30.50 | 1,292 |
| 0.75 | 4 | 10.75 | 266 | 20.75 | 726 | 30.75 | 1,308 |
| 1.00 | 7 | 11.00 | 275 | 21.00 | 739 | 31.00 | 1,323 |
| 1.25 | 10 | 11.25 | 285 | 21.25 | 753 | 31.25 | 1,339 |
| 1.50 | 13 | 11.50 | 295 | 21.50 | 766 | 31.50 | 1,355 |
| 1.75 | 16 | 11.75 | 305 | 21.75 | 779 | 31.75 | 1,371 |
| 2.00 | 20 | 12.00 | 315 | 22.00 | 793 | 32.00 | 1,387 |
| 2.25 | 24 | 12.25 | 325 | 22.25 | 807 | 32.25 | 1,403 |
| 2.50 | 28 | 12.50 | 335 | 22.50 | 820 | 32.50 | 1,419 |
| 2.75 | 33 | 12.75 | 345 | 22.75 | 834 | 32.75 | 1,435 |
| 3.00 | 37 | 13.00 | 356 | 23.00 | 848 | 33.00 | 1,451 |
| 3.25 | 42 | 13.25 | 366 | 23.25 | 862 | 33.25 | 1,467 |
| 3.50 | 47 | 13.50 | 377 | 23.50 | 876 | 33.50 | 1,483 |
| 3.75 | 53 | 13.75 | 388 | 23.75 | 890 | 33.75 | 1,499 |
| 4.00 | 58 | 14.00 | 399 | 24.00 | 904 | 34.00 | 1,515 |
| 4.25 | 64 | 14.25 | 409 | 24.25 | 918 | 34.25 | 1,532 |
| 4.50 | 70 | 14.50 | 421 | 24.50 | 932 | 34.50 | 1,548 |
| 4.75 | 76 | 14.75 | 432 | 24.75 | 947 | 34.75 | 1,564 |
| 5.00 | 82 | 15.00 | 443 | 25.00 | 961 | 35.00 | 1,581 |
| 5.25 | 88 | 15.25 | 454 | 25.25 | 976 | 35.25 | 1,597 |
| 5.50 | 95 | 15.50 | 466 | 25.50 | 990 | 35.50 | 1,614 |
| 5.75 | 101 | 15.75 | 477 | 25.75 | 1,005 | 35.75 | 1,630 |
| 6.00 | 108 | 16.00 | 489 | 26.00 | 1,019 | 36.00 | 1,647 |
| 6.25 | 115 | 16.25 | 501 | 26.25 | 1,034 | 36.25 | 1,663 |
| 6.50 | 122 | 16.50 | 512 | 26.50 | 1,049 | 36.50 | 1,680 |
| 6.75 | 130 | 16.75 | 524 | 26.75 | 1,064 | 36.75 | 1,697 |
| 7.00 | 137 | 17.00 | 536 | 27.00 | 1,078 | 37.00 | 1,713 |
| 7.25 | 145 | 17.25 | 548 | 27.25 | 1,093 | 37.25 | 1,730 |
| 7.50 | 153 | 17.50 | 560 | 27.50 | 1,108 | 37.50 | 1,747 |
| 7.75 | 161 | 17.75 | 573 | 27.75 | 1,123 | 37.75 | 1,764 |
| 8.00 | 169 | 18.00 | 585 | 28.00 | 1,138 | 38.00 | 1,780 |
| 8.25 | 177 | 18.25 | 597 | 28.25 | 1,154 | 38.25 | 1,797 |
| 8.50 | 185 | 18.50 | 610 | 28.50 | 1,169 | 38.50 | 1,814 |
| 8.75 | 194 | 18.75 | 622 | 28.75 | 1,184 | 38.75 | 1,831 |
| 9.00 | 202 | 19.00 | 635 | 29.00 | 1,199 | 39.00 | 1,848 |
| 9.25 | 211 | 19.25 | 648 | 29.25 | 1,215 | 39.25 | 1,865 |
| 9.50 | 220 | 19.50 | 661 | 29.50 | 1,230 | 39.50 | 1,882 |
| 9.75 | 229 | 19.75 | 674 | 29.75 | 1,245 | 39.75 | 1,899 |
| 10.00 | 238 | 20.00 | 687 | 30.00 | 1,261 | 40.00 | 1,916 |

This gage table shows OUTAGE volumes (volume of vapor space above the liquid surface).
 Distances are measured downward from the shell-full (zero-outage) level to the surface of the liquid.

TEXANA TANK CAR & MFG., LTD.

Gage Table Number: NTLX 2400
 Shell Full Capacity: 5,806 gal.
 Car Specification: DOT 111A100W1
 Tank Style: Straight cylindrical tank
 Tank Head Diameter: 108.0365 in.
 Tank Slope: 0 in/ft

Table Developed on: 6/7/06
 Printed on 6/7/06
 Printed by: R CALVIT
 Lining Thickness: 0 in.
 Volume of Internal Components: 0 gal.
 Manway Volume in Capacity: 0 gal.

Page 2

| Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons |
|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|
| 40.25 | 1,933 | 50.25 | 2,634 | 60.25 | 3,347 | 70.25 | 4,040 |
| 40.50 | 1,950 | 50.50 | 2,652 | 60.50 | 3,365 | 70.50 | 4,057 |
| 40.75 | 1,967 | 50.75 | 2,670 | 60.75 | 3,382 | 70.75 | 4,073 |
| 41.00 | 1,985 | 51.00 | 2,688 | 61.00 | 3,400 | 71.00 | 4,090 |
| 41.25 | 2,002 | 51.25 | 2,705 | 61.25 | 3,418 | 71.25 | 4,107 |
| 41.50 | 2,019 | 51.50 | 2,723 | 61.50 | 3,435 | 71.50 | 4,124 |
| 41.75 | 2,036 | 51.75 | 2,741 | 61.75 | 3,453 | 71.75 | 4,140 |
| 42.00 | 2,054 | 52.00 | 2,759 | 62.00 | 3,470 | 72.00 | 4,157 |
| 42.25 | 2,071 | 52.25 | 2,777 | 62.25 | 3,488 | 72.25 | 4,173 |
| 42.50 | 2,088 | 52.50 | 2,795 | 62.50 | 3,506 | 72.50 | 4,190 |
| 42.75 | 2,106 | 52.75 | 2,812 | 62.75 | 3,523 | 72.75 | 4,206 |
| 43.00 | 2,123 | 53.00 | 2,830 | 63.00 | 3,541 | 73.00 | 4,223 |
| 43.25 | 2,140 | 53.25 | 2,848 | 63.25 | 3,558 | 73.25 | 4,239 |
| 43.50 | 2,158 | 53.50 | 2,866 | 63.50 | 3,576 | 73.50 | 4,255 |
| 43.75 | 2,175 | 53.75 | 2,884 | 63.75 | 3,593 | 73.75 | 4,272 |
| 44.00 | 2,193 | 54.00 | 2,902 | 64.00 | 3,611 | 74.00 | 4,288 |
| 44.25 | 2,210 | 54.25 | 2,920 | 64.25 | 3,628 | 74.25 | 4,304 |
| 44.50 | 2,228 | 54.50 | 2,937 | 64.50 | 3,646 | 74.50 | 4,321 |
| 44.75 | 2,245 | 54.75 | 2,955 | 64.75 | 3,663 | 74.75 | 4,337 |
| 45.00 | 2,263 | 55.00 | 2,973 | 65.00 | 3,680 | 75.00 | 4,353 |
| 45.25 | 2,280 | 55.25 | 2,991 | 65.25 | 3,698 | 75.25 | 4,369 |
| 45.50 | 2,298 | 55.50 | 3,009 | 65.50 | 3,715 | 75.50 | 4,385 |
| 45.75 | 2,315 | 55.75 | 3,027 | 65.75 | 3,732 | 75.75 | 4,401 |
| 46.00 | 2,333 | 56.00 | 3,044 | 66.00 | 3,750 | 76.00 | 4,417 |
| 46.25 | 2,351 | 56.25 | 3,062 | 66.25 | 3,767 | 76.25 | 4,433 |
| 46.50 | 2,368 | 56.50 | 3,080 | 66.50 | 3,784 | 76.50 | 4,449 |
| 46.75 | 2,386 | 56.75 | 3,098 | 66.75 | 3,802 | 76.75 | 4,464 |
| 47.00 | 2,403 | 57.00 | 3,116 | 67.00 | 3,819 | 77.00 | 4,480 |
| 47.25 | 2,421 | 57.25 | 3,134 | 67.25 | 3,836 | 77.25 | 4,496 |
| 47.50 | 2,439 | 57.50 | 3,151 | 67.50 | 3,853 | 77.50 | 4,512 |
| 47.75 | 2,457 | 57.75 | 3,169 | 67.75 | 3,870 | 77.75 | 4,527 |
| 48.00 | 2,474 | 58.00 | 3,187 | 68.00 | 3,887 | 78.00 | 4,543 |
| 48.25 | 2,492 | 58.25 | 3,205 | 68.25 | 3,904 | 78.25 | 4,558 |
| 48.50 | 2,510 | 58.50 | 3,223 | 68.50 | 3,921 | 78.50 | 4,574 |
| 48.75 | 2,527 | 58.75 | 3,240 | 68.75 | 3,938 | 78.75 | 4,589 |
| 49.00 | 2,545 | 59.00 | 3,258 | 69.00 | 3,955 | 79.00 | 4,604 |
| 49.25 | 2,563 | 59.25 | 3,276 | 69.25 | 3,972 | 79.25 | 4,620 |
| 49.50 | 2,581 | 59.50 | 3,294 | 69.50 | 3,989 | 79.50 | 4,635 |
| 49.75 | 2,598 | 59.75 | 3,311 | 69.75 | 4,006 | 79.75 | 4,650 |
| 50.00 | 2,616 | 60.00 | 3,329 | 70.00 | 4,023 | 80.00 | 4,665 |

This gage table shows OUTAGE volumes (volume of vapor space above the liquid surface).
 Distances are measured downward from the shell-full (zero-outage) level to the surface of the liquid.

TEXANA TANK CAR & MFG., LTD.

Gage Table Number: NTLX 2400
 Shell Full Capacity: 5,806 gal.
 Car Specification: DOT 111A100W1
 Tank Style: Straight cylindrical tank
 Tank Head Diameter: 108.0365 in.
 Tank Slope: 0 in/ft

Table Developed on: 6/7/06
 Printed on 6/7/06
 Printed by: R CALVIT
 Lining Thickness: 0 in.
 Volume of Internal Components: 0 gal.
 Manway Volume in Capacity: 0 gal.

| Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons | Dist. Inches | Outage Gallons |
|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|-----------------|-------------------|
| 80.25 | 4,680 | 90.25 | 5,231 | 100.25 | 5,644 | | |
| 80.50 | 4,695 | 90.50 | 5,244 | 100.50 | 5,652 | | |
| 80.75 | 4,710 | 90.75 | 5,256 | 100.75 | 5,660 | | |
| 81.00 | 4,725 | 91.00 | 5,268 | 101.00 | 5,668 | | |
| 81.25 | 4,740 | 91.25 | 5,280 | 101.25 | 5,675 | | |
| 81.50 | 4,755 | 91.50 | 5,292 | 101.50 | 5,682 | | |
| 81.75 | 4,770 | 91.75 | 5,304 | 101.75 | 5,690 | | |
| 82.00 | 4,784 | 92.00 | 5,315 | 102.00 | 5,697 | | |
| 82.25 | 4,799 | 92.25 | 5,327 | 102.25 | 5,704 | | |
| 82.50 | 4,814 | 92.50 | 5,339 | 102.50 | 5,710 | | |
| 82.75 | 4,828 | 92.75 | 5,350 | 102.75 | 5,717 | | |
| 83.00 | 4,843 | 93.00 | 5,361 | 103.00 | 5,723 | | |
| 83.25 | 4,857 | 93.25 | 5,373 | 103.25 | 5,729 | | |
| 83.50 | 4,871 | 93.50 | 5,384 | 103.50 | 5,736 | | |
| 83.75 | 4,886 | 93.75 | 5,395 | 103.75 | 5,741 | | |
| 84.00 | 4,900 | 94.00 | 5,406 | 104.00 | 5,747 | | |
| 84.25 | 4,914 | 94.25 | 5,417 | 104.25 | 5,753 | | |
| 84.50 | 4,928 | 94.50 | 5,427 | 104.50 | 5,758 | | |
| 84.75 | 4,942 | 94.75 | 5,438 | 104.75 | 5,763 | | |
| 85.00 | 4,956 | 95.00 | 5,449 | 105.00 | 5,768 | | |
| 85.25 | 4,970 | 95.25 | 5,459 | 105.25 | 5,773 | | |
| 85.50 | 4,984 | 95.50 | 5,469 | 105.50 | 5,777 | | |
| 85.75 | 4,997 | 95.75 | 5,480 | 105.75 | 5,781 | | |
| 86.00 | 5,011 | 96.00 | 5,490 | 106.00 | 5,785 | | |
| 86.25 | 5,024 | 96.25 | 5,500 | 106.25 | 5,789 | | |
| 86.50 | 5,038 | 96.50 | 5,510 | 106.50 | 5,793 | | |
| 86.75 | 5,051 | 96.75 | 5,520 | 106.75 | 5,796 | | |
| 87.00 | 5,065 | 97.00 | 5,529 | 107.00 | 5,799 | | |
| 87.25 | 5,078 | 97.25 | 5,539 | 107.25 | 5,801 | | |
| 87.50 | 5,091 | 97.50 | 5,548 | 107.50 | 5,803 | | |
| 87.75 | 5,104 | 97.75 | 5,558 | 107.75 | 5,805 | | |
| 88.00 | 5,117 | 98.00 | 5,567 | 108.00 | 5,806 | | |
| 88.25 | 5,130 | 98.25 | 5,576 | | | | |
| 88.50 | 5,143 | 98.50 | 5,585 | | | | |
| 88.75 | 5,156 | 98.75 | 5,594 | | | | |
| 89.00 | 5,169 | 99.00 | 5,603 | | | | |
| 89.25 | 5,182 | 99.25 | 5,611 | | | | |
| 89.50 | 5,194 | 99.50 | 5,620 | | | | |
| 89.75 | 5,207 | 99.75 | 5,628 | | | | |
| 90.00 | 5,219 | 100.00 | 5,636 | | | | |

This gage table shows OUTAGE volumes (volume of vapor space above the liquid surface).
 Distances are measured downward from the shell-full (zero-outage) level to the surface of the liquid.